Statement of Basis of the Federal Operating Permit

The Lubrizol Corporation

Site Name: Blending Storage and Loading Physical Location: 41 Tidal Road Nearest City: Deer Park County: Harris

> Permit Number: O1581 Project Type: Renewal

Standard Industrial Classification (SIC) Code: 2869 SIC Name: Industrial Organic Chemicals

This Statement of Basis sets forth the legal and factual basis for the draft permit conditions in accordance with 30 TAC §122.201(a)(4). Per 30 TAC §§ 122.241 and 243, the permit holder has submitted an application under § 122.134 for permit renewal. This document may include the following information:

A description of the facility/area process description;

A basis for applying permit shields;

A list of the federal regulatory applicability determinations;

A table listing the determination of applicable requirements;

A list of the New Source Review Requirements;

The rationale for periodic monitoring methods selected;

The rationale for compliance assurance methods selected:

A compliance status; and

A list of available unit attribute forms.

Prepared on: May 17, 2017

Operating Permit Basis of Determination

Permit Area Process Description

Lubrizol Corporation's Deer Park plant produces lubricating products by mixing one or more lube oil additives, referred to as "intermediates" with a base lubricating oil. Finished blends fall into one of seven major groups:

- Antioxidant additive (corrosion inhibitor)
- Anglamol friction modifier
- Calcium phenate detergent
- Calcium sulfonate detergent
- Dispersants
- Extreme pressure additive
- Mercaptan/H₂S producing blend (BL-17 and BL-34)

The intermediates described above are high molecular weight, low vapor pressure volatile organic compounds (VOCs). These intermediates are transferred to the blend vessels through a network of pipelines and manifold systems. Occasionally small quantities of intermediates in drums are added to a blend vessel but the vast majority of the blend components reach the blend vessel via piping.

Blend process times vary around a range of from 6 hours to 72 hours for small to larger vessels respectively. Lubrizol operates each blend at a slightly different temperature. The normal blend temperature is approximately 180 degrees F. Each blend vessel is equipped with an agitator that provides continual mixing of the blend.

Most blend vessels vent directly to the atmosphere throughout the blend process. This is not a significant source of emissions due to the low vapor pressures of the blend components. Blend systems BL-17 and BL-34 are routed to a caustic scrubber followed by incineration (FI-02) for the control of mercaptan and hydrogen sulfide (H_2S) emissions.

Finished blends are put in drums, pumped to storage or pumped directly to tank truck or railcar for transport.

FOPs at Site

The "application area" consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O1929, O1930, O1931, O1932, O1933, O1934, O1935, O2191

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO2, PM, NOX, HAPS, CO

Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as "applicable requirements") that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires

adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - o New Source Review Authorization Requirements
 - Compliance Requirements
 - Protection of Stratosphere Ozone
 - Permit Location
 - Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - o New Source Review Authorization References
 - o Compliance Plan
 - Alternative Requirements
- Appendix A
 - o Acronym list

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with

applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the "index number," detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed either before or after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit

Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3.A for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	No
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	No
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	No
40 CFR Part 63 - NESHAPs for Source Categories	No
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CSAPR (Cross-State Air Pollution Rule)	No

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

- 1. Office activities such as photocopying, blueprint copying, and photographic processes.
- 2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
- 3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
- 4. Outdoor barbecue pits, campfires, and fireplaces.
- 5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
- 6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
- 7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
- 8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
- 9. Vehicle exhaust from maintenance or repair shops.
- 10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
- 11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
- 12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
- 13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
- 14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
- 15. Well cellars.
- 16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
- 17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
- 18. Equipment used exclusively for the melting or application of wax.
- 19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
- 20. Shell core and shell mold manufacturing machines.
- 21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
- 22. Equipment used for inspection of metal products.

- 23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
- 24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
- 25. Battery recharging areas.
- 26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit

attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*
AA-800	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AA-800	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AG-1	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AG-1	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AG-13	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance
	VOCS		with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
AG-13	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
AG-14	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
		OCs AI	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AG-14	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AG-15	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
AG-15	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
AG-2	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AG-2	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb	Subpart Kb Storage Capacity = Capacity is greater than or	Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AG-4	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	Arternate Control Requiren	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
AG-4	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)

Unit ID	Regulation	Index Number	Basis of Determination*
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
AG-6	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AG-6	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AG-7	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AG-7	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
)	Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AG-8	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AG-8	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AG-9	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
AG-9	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
AM-1	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
AM-1	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
AM-12	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
AM-12	40 CFR Part 60, Subpart Kb	Subpart Vh	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
AM-13	30 TAC Chapter	15, Storage of	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
AM-13	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia

Unit ID	Regulation	Index Number	Basis of Determination*
AM-14	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
AM-14	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
AM-2	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
AM-2	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
AM-3	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
AM-3	40 CFR Part 60,	O CFR Part 60, 60KB-0001 Product Stored = Volatile organic liquid	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
AM-4		R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons

Unit ID	Regulation	Index Number	Basis of Determination*
AM-4	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb	rt Kb	Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
ARM-1	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
ARM-1	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
B-6	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	age of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
B-6	40 CFR Part 60,	hnart Vh	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
BD-1	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	Cs With applicable control requirements or e Tank Description = Tank does not require True Vapor Pressure = True vapor pressure	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
BD-1	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
BL-12	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
BL-12	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
BL-13	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
BL-13	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
CC-500	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
		orage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-500		apart Kh	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CC-501	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	orage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-501	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CC-502	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-502	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CC-506	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	5, Storage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-506	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CC-507	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-507	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CC-512	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	IOCo A	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-512	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CC-513	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-513	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CC-800	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
CC-800	40 CFR Part 60,	phart Kh	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
CR-1	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
CR-1	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)

Unit ID	Regulation	Index Number	Basis of Determination*
CR-2	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
CR-2	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
D-1	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-1	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-10	30 TAC Chapter	Storage of	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
			Control Device Type = Direct-flame incinerator
D-100	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-100	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)

Unit ID	Regulation	Index Number	Basis of Determination*
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-101	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-101	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-102	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-102	40 CFR Part 60, Subpart Kb	60, 60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-103	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-103	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-104	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-104	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
D-11	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-11	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-110	30 TAC Chapter 115, Storage of VOCs	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-110	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-111	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-112	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	Alternate Control Requirement = Not	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.

Unit ID	Regulation	Index Number	Basis of Determination*
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-113	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-114	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-115	30 TAC Chapter 115, Storage of VOCs	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
D-116	30 TAC Chapter	Storage of Alternate Control I	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-117	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	torage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-118	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-119	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-12	30 TAC Chapter 115, Storage of VOCs		Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-12	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-120	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-121	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-122	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-123	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-124	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-125	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-126	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	orage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 40,000 gallons
D-127	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-128	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-129	30 TAC Chapter 115, Storage of VOCs	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-13	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
		Tank Description =	Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-13	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-130	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-131	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-132	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-133	30 TAC Chapter 115, Storage of VOCs		Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
D-14	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-14	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-15	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-15	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-16	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-16	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-17	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-17	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-18	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-18	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia

Unit ID	Regulation	Index Number	Basis of Determination*
D-19	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-19	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-2	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-2	40 CFR Part 60, Subpart Kb	0, 60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-20	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-20	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-21	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 40,000 gallons
D-21	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-22	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-23	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-23	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-24	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
		ge of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-24	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-25	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-25	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-26	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-26	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-27	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-27	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-29	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-29	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-3	30 TAC Chapter	R5112-0007	Today's Date = Today's date is before March 1, 2013.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
			Control Device Type = Direct-flame incinerator
D-30	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-30	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-31	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	rage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-31	40 CFR Part 60, Subpart Kb	60KB-0007	Product Stored = Stored product other than volatile organic liquid or petroleum liquid
D-32	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-32	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-33	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.

Unit ID	Regulation	Index Number	Basis of Determination*
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-33	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-4	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-4	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-5	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-5	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-6	30 TAC Chapter	R5112-0007	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
			Control Device Type = Direct-flame incinerator

Unit ID	Regulation	Index Number	Basis of Determination*
D-60	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-60	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-61	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-61	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-62	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-62	40 CFR Part 60,	,	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-63	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 40,000 gallons
D-63	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-64	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-64	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-65	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-65	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-7	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-7	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia

Unit ID	Regulation	Index Number	Basis of Determination*
D-71	30 TAC Chapter 115, Storage of	R5112-0004	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement - Not using an alternate method for demonstrating and degementing continuous compliance.
	VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-71	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-72	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-72	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-73	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-73	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-74	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 40,000 gallons
D-74	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-75	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-75	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-76	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-76	40 CFR Part 60,	60, 60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-78	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-78	40 CFR Part 60, Subpart Kb		Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-79	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-79	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-8	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-8	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-80	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-80	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-81	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons

Unit ID	Regulation	Index Number	Basis of Determination*
D-81	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-82	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
D-82	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-83	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
D-83	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-84	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
D-84	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-85	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.

Unit ID	Regulation	Index Number	Basis of Determination*
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-85	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-86	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-86	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-87	30 TAC Chapter 115, Storage of VOCs		Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-87	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-88	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-88	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)

Unit ID	Regulation	Index Number	Basis of Determination*
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-89	30 TAC Chapter 115, Storage of	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-89	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-9	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-9	40 CFR Part 60, Subpart Kb	0, 60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-90	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-90	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-91	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	Storage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-91	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-92	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-92	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-93	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-93	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-94	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	Alternate Cont	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-94	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb	rt Kb	Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia

Unit ID	Regulation	Index Number	Basis of Determination*
D-95	30 TAC Chapter 115, Storage of VOCs	R5112-0004	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-95	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
	Suspect No		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-96	30 TAC Chapter 115, Storage of	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-96	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-97	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
D-97	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-98	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 40,000 gallons
D-98	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
D-99	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
FO-44	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
FO-44	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-1	30 TAC Chapter 115, Storage of VOCs		Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-1	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-10	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-10	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)

Unit ID	Regulation	Index Number	Basis of Determination*
I-11	30 TAC Chapter 115, Storage of VOCs	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-11	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-12	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-12	40 CFR Part 60, Subpart Kb	60KB-0001	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-13	30 TAC Chapter	Storage of	Today's Date = Today's date is March 1, 2013 or later.
	VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-13	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-14	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons

Unit ID	Regulation	Index Number	Basis of Determination*
I-14	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-15	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-15	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-16	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-16	40 CFR Part 60, Subpart Kb		Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-17	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-17	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb	art Kb	Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-18	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of	ge of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-18	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-19	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-19	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-2	30 TAC Chapter 115, Storage of VOCs		Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-2	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-21	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-21	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid

Unit ID	Regulation	Index Number	Basis of Determination*
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-22	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-22	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-23	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-23	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-24	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-24	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb	part Kb	Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia

Unit ID	Regulation	Index Number	Basis of Determination*
I-25	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
I-25	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-26	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
I-26	40 CFR Part 60, Subpart Kb	, 60KB-0003	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-27	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
I-27	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-28	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
I-28	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
I-3	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-3	40 CFR Part 60,	0, 60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-5	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-5	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-6	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-6	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-7	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-7	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-8	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-8	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
I-9	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
I-9	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
KO-AA800	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
KO-AA800	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
KOD-70	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
KOD-70	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
M-48	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
OS-10	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
OS-10	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
OS-11	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
OS-11	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia

Unit ID	Regulation	Index Number	Basis of Determination*
OS-20	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
OS-20	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
P-36A	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
P-36A	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
R-5	30 TAC Chapter	Storage of	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
R-5	40 CFR Part 60,	O, 60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
RA-4	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons

Unit ID	Regulation	Index Number	Basis of Determination*
RA-4	40 CFR Part 60,	, 60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
RA-5	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
RA-5	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
RA-6	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
RA-6	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
RA-8	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	orage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
RA-8	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb	Kb	Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia

Unit ID	Regulation	Index Number	Basis of Determination*
RA-9	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
RA-9	40 CFR Part 60,	60KB-0002	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 10,600 gallons (40,000 liters) but less than 19,800 gallons (75,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SA-1	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SA-2	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SA-2	40 CFR Part 60,	recut VIb	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SA-3	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons

Unit ID	Regulation	Index Number	Basis of Determination*
SA-3	40 CFR Part 60,	60, 60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SA-4	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SA-4	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SA-5	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SA-5	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SA-6	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SA-6	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb	rt Kb	Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia

Unit ID	Regulation	Index Number	Basis of Determination*
SA-7	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SA-7	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SAB-1	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SAB-1	40 CFR Part 60, Subpart Kb	60, 60KB-0003	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SAB-2	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SS-10	30 TAC Chapter	15, Storage of Alternate Control Requirement = Not using an alternate method for demonstrate Alternate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using an alternate method for demonstrate Control Requirement = Not using a new figure Control Requirement = Not	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-10	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia

Unit ID	Regulation	Index Number	Basis of Determination*
SS-11	30 TAC Chapter 115, Storage of VOCs		Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-11	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-12	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-12	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-13	30 TAC Chapter 115, Storage of		Today's Date = Today's date is March 1, 2013 or later.
	VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-13	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-16	30 TAC Chapter 115, Storage of	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-16	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-20	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-20	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-22	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	orage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-22	40 CFR Part 60,		Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-23	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	Storage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-23	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-24	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-24	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-25	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-25	40 CFR Part 60, Subpart Kb	60KB-0004	Product Stored = Volatile organic liquid
			Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-29	30 TAC Chapter 115, Storage of VOCs		Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-3	30 TAC Chapter 115, Storage of VOCs	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SS-3	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb	part Kb	Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia

Unit ID	Regulation	Index Number	Basis of Determination*
SS-35	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-36	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-4	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SS-4	40 CFR Part 60,), 60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SS-5	30 TAC Chapter 115, Storage of VOCs	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
			Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SS-5	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia

Unit ID	Regulation	Index Number	Basis of Determination*
SS-6	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SS-6	40 CFR Part 60,	60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SS-7	30 TAC Chapter	R5112-0003	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 25,000 gallons but less than or equal to 40,000 gallons
SS-7	40 CFR Part 60,	0, 60KB-0003	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
SS-8	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-8	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SS-9	30 TAC Chapter	R5112-0004	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs	, Storage of	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 40,000 gallons
SS-9	40 CFR Part 60,	60KB-0004	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)
			Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
SSB-1	30 TAC Chapter	R5112-0002	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
SSB-1	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
WO-AA800	30 TAC Chapter	Storage of	Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
WO-AA800	40 CFR Part 60,	CFR Part 60, bpart Kb	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
WO-CC800	30 TAC Chapter		Today's Date = Today's date is March 1, 2013 or later.
	115, Storage of VOCs		Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.
			Tank Description = Tank does not require emission controls
			True Vapor Pressure = True vapor pressure is less than 1.0 psia
			Product Stored = VOC other than crude oil or condensate
			Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
WO-CC800	40 CFR Part 60,	60KB-0001	Product Stored = Volatile organic liquid
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
LOADA11	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	1		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.

Unit ID	Regulation	Index Number	Basis of Determination*
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA12	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA13	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA14	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 60		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA15	30 TAC Chapter 115, Loading and Unloading of VOC	15, Loading and nloading of	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA16	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA17	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA18	30 TAC Chapter 115, Loading and		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA19	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA20	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, voc		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA21	30 TAC Chapter 115, Loading and Unloading of VOC	Loading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA23	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
		g of	Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA24	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.

Unit ID	Regulation	Index Number	Basis of Determination*
LOADA26	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	Voc		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA27	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA33	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA36	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADA38	30 TAC Chapter 115, Loading and	, Loading and oading of	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB11	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.

Unit ID	Regulation	Index Number	Basis of Determination*
LOADB12	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	100		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB13	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	VOC		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB14	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	VOC		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB15	30 TAC Chapter 115, Loading and Unloading of VOC		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB16	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	1,00		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB17	115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 00		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB18	30 TAC Chapter	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing

Unit ID	Regulation	Index Number	Basis of Determination*
	115, Loading and		facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 00		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB19	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 60		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB20	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB21	30 TAC Chapter 115, Loading and	ng and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB23	30 TAC Chapter 115, Loading and	oading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB24	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB26	30 TAC Chapter 115, Loading and Unloading of	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.

Unit ID	Regulation	Index Number	Basis of Determination*
	VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB27	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	1,00		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB33	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	1,00		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB36	30 TAC Chapter 115, Loading and	g and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADB38	30 TAC Chapter 115, Loading and	Loading and adding of A	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE1	30 TAC Chapter 115, Loading and	5, Loading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE10	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE11	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, , , ,		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE12	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE13	30 TAC Chapter 115, Loading and		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	VOC		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE15	30 TAC Chapter 115, Loading and Unloading of VOC	oading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE16	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE17	30 TAC Chapter	R5211-0005	Chapter 115 Control Device Type = No control device.
	115, Loading and Unloading of VOC	oading of	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.

Unit ID	Regulation	Index Number	Basis of Determination*
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.
			Control Options = Vapor balance system.
LOADE18	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE19	30 TAC Chapter 115, Loading and	ing and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE2	30 TAC Chapter 115, Loading and Unloading of VOC	ading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE20	30 TAC Chapter 115, Loading and	ding and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE21	30 TAC Chapter 115, Loading and	oading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.

Unit ID	Regulation	Index Number	Basis of Determination*
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE23	30 TAC Chapter	R5211-0004	Chapter 115 Control Device Type = No control device.
	115, Loading and Unloading of VOC		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	, 00		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.
			Control Options = Pressurized loading system.
LOADE28	30 TAC Chapter	R5211-0004	Chapter 115 Control Device Type = No control device.
	115, Loading and Unloading of VOC		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Voc		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.
			Control Options = Vapor balance system.
LOADE3	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE4	30 TAC Chapter 115, Loading and	5, Loading and loading of	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.

Unit ID	Regulation	Index Number	Basis of Determination*
LOADE5	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-0005	Chapter 115 Control Device Type = No control device.
			Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	, 30		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.
			Control Options = Vapor balance system.
LOADE6	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 30		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE7	30 TAC Chapter 115, Loading and Unloading of VOC	g and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE8	30 TAC Chapter 115, Loading and Unloading of VOC	, Loading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADE9	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 30		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-01	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.

Unit ID	Regulation	Index Number	Basis of Determination*
	Unloading of		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	VOC		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-02	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	100		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-03	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-04	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-05	30 TAC Chapter 115, Loading and Unloading of VOC	ling and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 5 0		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-06	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-07	30 TAC Chapter 115, Loading and	5, Loading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-08	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 50		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-09	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-10	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTT-12	30 TAC Chapter	5, Loading and loading of	Chapter 115 Control Device Type = No control device.
	115, Loading and Unloading of VOC		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.
			Control Options = Pressurized loading system.
LOADTTACID	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	VOC		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.

Unit ID	Regulation	Index Number	Basis of Determination*
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTTBOVR	30 TAC Chapter 115, Loading and	R5211-0002	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Loading less than 20,000 gallons per day.
LOADTTSHTD	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADTTWOVR	30 TAC Chapter 115, Loading and Unloading of VOC	g and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW1	30 TAC Chapter 115, Loading and	5, Loading and loading of	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, , ,		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW10	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW11	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.

Unit ID	Regulation	Index Number	Basis of Determination*
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW12	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW13	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW15	30 TAC Chapter 115, Loading and Unloading of VOC	ng and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW16	30 TAC Chapter 115, Loading and Unloading of VOC	ling and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW17	30 TAC Chapter	R5211-0005	Chapter 115 Control Device Type = No control device.
	115, Loading and Unloading of VOC		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	, 50		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Options = Vapor balance system.
LOADW18	30 TAC Chapter 115, Loading and		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW19	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW2	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW20	30 TAC Chapter 115, Loading and Unloading of VOC	, Loading and coading of	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW21	30 TAC Chapter 115, Loading and	15, Loading and fa	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW28	30 TAC Chapter	R5211-0004	Chapter 115 Control Device Type = No control device.
	115, Loading and Unloading of VOC		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.
			Control Options = Vapor balance system.
LOADW3	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW4	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC	f	Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	, 5 0		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW5	30 TAC Chapter	R5211-0005	Chapter 115 Control Device Type = No control device.
	115, Loading and Unloading of VOC		Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Vapor Tight = All liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
			Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.
			Control Options = Vapor balance system.
LOADW6	115, Loading and	Loading and	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW7	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.

Unit ID	Regulation	Index Number	Basis of Determination*
	Unloading of		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	VOC		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW8	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	VOC		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
LOADW9	30 TAC Chapter 115, Loading and	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	100		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Loading and unloading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
NBLNDDRUM	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-0001	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
			Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
			Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
SBLNDDRUM	30 TAC Chapter 115, Loading and	, Loading and oading of	Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.
	Unloading of VOC		Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.
	Voc		Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.
			Transfer Type = Only loading.
			True Vapor Pressure = True vapor pressure less than 0.5 psia.
B-9	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-1	30 TAC Chapter 115, Vent Gas		Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the

Unit ID	Regulation	Index Number	Basis of Determination*
			applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-10	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-17	30 TAC Chapter	R5121-0002	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
BL-18	30 TAC Chapter	R5121-0002	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
BL-2	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-23	30 TAC Chapter 115, Vent Gas	, Vent Gas	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-24	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-25	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.

Unit ID	Regulation	Index Number	Basis of Determination*
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-26	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-27	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-28	30 TAC Chapter 115, Vent Gas	Vent Gas	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-29	30 TAC Chapter 115, Vent Gas Controls	Vent Gas	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-3	30 TAC Chapter 115, Vent Gas		Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-30	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-31	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.

Unit ID	Regulation	Index Number	Basis of Determination*
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-32	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-33	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-34	30 TAC Chapter	R5121-0002	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
BL-36	30 TAC Chapter	Vent Gas	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-6	30 TAC Chapter 115, Vent Gas	Vent Gas	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-7	30 TAC Chapter 115, Vent Gas	ent Gas	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).

Unit ID	Regulation	Index Number	Basis of Determination*
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-8	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
BL-9	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
D-137	30 TAC Chapter	R5121-0001	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls	as	Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = Either the VOC concentration or emission rate is greater than the applicable exemption limit at maximum actual operating conditions or the alternate recordkeeping requirements of 30 TAC § 115.126(4) are not being selected.
D-67	30 TAC Chapter	R5121-0001	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
D-68	30 TAC Chapter	R5121-0001	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.

Unit ID	Regulation	Index Number	Basis of Determination*
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
D-69	30 TAC Chapter	R5121-0001	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
D-70	30 TAC Chapter		Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
I-4	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
SBD-PV1	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
SBD-PV2	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.

Unit ID	Regulation	Index Number	Basis of Determination*
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
SBD-PV3	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
SS-1	30 TAC Chapter 115, Vent Gas	R5121-0001	Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
	Controls		Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
SS-2	30 TAC Chapter	15, Vent Gas	Alternate Control Requirement = Alternate control is not used.
	115, Vent Gas Controls		Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.
			Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.
			Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
			Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).
			VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.

^{* -} The "unit attributes" or operating conditions that determine what requirements apply

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	it Federal Operating Permit(FOP)	
Issued Prior to new Construction or modification	For initial permit with application shield, can be issued	
of an existing facility	after operation commences; significant revisions require	
	approval prior to operation.	
Authorizes air emissions	Codifies existing applicable requirements, does not	
	authorize new emissions	
Ensures issued permits are protective of the	Applicable requirements listed in permit are used by	
environment and human health by conducting a	the inspectors to ensure proper operation of the site as	
health effects review and that requirement for	authorized. Ensures that adequate monitoring is in	
best available control technology (BACT) is	place to allow compliance determination with the FOP.	
implemented.		
Up to two Public notices may be required.	One public notice required. Opportunity for public	
Opportunity for public comment and contested	comments. No contested case hearings.	
case hearings for some authorizations.		
Applies to all point source emissions in the state.	Applies to all major sources and some non-major	
	sources identified by the EPA.	
Applies to facilities: a portion of site or	One or multiple FOPs cover the entire site (consists of	
individual emission sources	multiple facilities)	
Permits include terms and conditions under	Permits include terms and conditions that specify the	
which the applicant must construct and operate	general operational requirements of the site; and also	
its various equipment and processes on a facility	include codification of all applicable requirements for	
basis.	emission units at the site.	
Opportunity for EPA review for Federal	Opportunity for EPA review, Affected states review, and	
Prevention of Significant Deterioration (PSD) and	a Public petition period for every FOP.	
Nonattainment (NA) permits for major sources.		
Permits have a table listing maximum emission	Permit has an applicable requirements table and	
limits for pollutants	Periodic Monitoring (PM) / Compliance Assurance	
	Monitoring (CAM) tables which document applicable	
	monitoring requirements.	
Permits can be altered or amended upon	Permits can be revised through several revision	
application by company. Permits must be issued	processes, which provide for different levels of public	
before construction or modification of facilities	notice and opportunity to comment. Changes that	
can begin.	would be significant revisions require that a revised	
	permit be issued before those changes can be operated.	
NSR permits are issued independent of FOP	FOP are independent of NSR permits, but contain a list	
requirements.	of all NSR permits incorporated by reference	

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

 $www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106 list/index 106. html$

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

The status of air permits and applications and a link to the Air Permits Remote Document Server is located at the following Web site:

www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.		
Authorization No.: 122494	Issuance Date: 10/01/2014	
Authorization No.: 131877	Issuance Date: 05/26/2015	
Authorization No.: 669	Issuance Date: 01/05/2012	
Permits By Rule (30 TAC Chapter 106) for the Application Area		
Number: 106.261	Version No./Date: 11/01/2003	
Number: 106.262	Version No./Date: 11/01/2003	
Number: 106.263	Version No./Date: 11/01/2001	
Number: 106.472	Version No./Date: 09/04/2000	

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the "Maximum Allowable Emission Rate Table", or "MAERT" for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a

relevant time period that are representative of the emission unit's compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Compliance Review

Site rating: <u>9.41 / Satisfactory</u> Company rating: <u>10.39 / Satisfactory</u>	
(High < 0.10 ; Satisfactory ≥ 0.10 and ≤ 55 ; Unsatisfactory > 55)	
2. Has the permit changed on the basis of the compliance history or site/company rating?	No
Site/Permit Area Compliance Status Review	
1. Were there any out-of-compliance units listed on Form OP-ACPS?	No
2. Is a compliance plan and schedule included in the permit?	No

1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on March 9, 2017.

Available Unit Attribute Forms

- OP-UA1 Miscellaneous and Generic Unit Attributes
- OP-UA2 Stationary Reciprocating Internal Combustion Engine Attributes
- OP-UA3 Storage Tank/Vessel Attributes
- OP-UA4 Loading/Unloading Operations Attributes
- OP-UA5 Process Heater/Furnace Attributes
- OP-UA6 Boiler/Steam Generator/Steam Generating Unit Attributes
- OP-UA7 Flare Attributes
- OP-UA8 Coal Preparation Plant Attributes
- OP-UA9 Nonmetallic Mineral Process Plant Attributes
- OP-UA10 Gas Sweetening/Sulfur Recovery Unit Attributes
- OP-UA11 Stationary Turbine Attributes
- OP-UA12 Fugitive Emission Unit Attributes
- OP-UA13 Industrial Process Cooling Tower Attributes
- OP-UA14 Water Separator Attributes
- OP-UA15 Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
- OP-UA16 Solvent Degreasing Machine Attributes
- OP-UA17 Distillation Unit Attributes
- OP-UA18 Surface Coating Operations Attributes
- OP-UA19 Wastewater Unit Attributes
- OP-UA20 Asphalt Operations Attributes
- OP-UA21 Grain Elevator Attributes
- OP-UA22 Printing Attributes
- OP-UA24 Wool Fiberglass Insulation Manufacturing Plant Attributes
- OP-UA25 Synthetic Fiber Production Attributes
- OP-UA26 Electroplating and Anodizing Unit Attributes
- OP-UA27 Nitric Acid Manufacturing Attributes
- OP-UA28 Polymer Manufacturing Attributes
- OP-UA29 Glass Manufacturing Unit Attributes
- OP-UA30 Kraft, Soda, Sulfite, and Stand-Alone Semichemical Pulp Mill Attributes
- OP-UA31 Lead Smelting Attributes
- OP-UA32 Copper and Zinc Smelting/Brass and Bronze Production Attributes

- OP-UA33 Metallic Mineral Processing Plant Attributes
- OP-UA34 Pharmaceutical Manufacturing
- OP-UA35 Incinerator Attributes
- OP-UA36 Steel Plant Unit Attributes
- OP-UA37 Basic Oxygen Process Furnace Unit Attributes
- OP-UA38 Lead-Acid Battery Manufacturing Plant Attributes
- OP-UA39 Sterilization Source Attributes
- OP-UA40 Ferroalloy Production Facility Attributes
- OP-UA41 Dry Cleaning Facility Attributes
- OP-UA42 Phosphate Fertilizer Manufacturing Attributes
- OP-UA43 Sulfuric Acid Production Attributes
- OP-UA44 Municipal Solid Waste Landfill/Waste Disposal Site Attributes
- OP-UA45 Surface Impoundment Attributes
- OP-UA46 Epoxy Resins and Non-Nylon Polyamides Production Attributes
- OP-UA47 Ship Building and Ship Repair Unit Attributes
- OP-UA48 Air Oxidation Unit Process Attributes
- OP-UA49 Vacuum-Producing System Attributes
- OP-UA50 Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur
- **Recovery Plant Attributes**
- OP-UA51 Dryer/Kiln/Oven Attributes
- OP-UA52 Closed Vent Systems and Control Devices
- OP-UA53 Beryllium Processing Attributes
- OP-UA54 Mercury Chlor-Alkali Cell Attributes
- OP-UA55 Transfer System Attributes
- OP-UA56 Vinyl Chloride Process Attributes
- OP-UA57 Cleaning/Depainting Operation Attributes
- OP-UA58 Treatment Process Attributes
- OP-UA59 Coke By-Product Recovery Plant Attributes
- OP-UA60 Chemical Manufacturing Process Unit Attributes
- OP-UA61 Pulp, Paper, or Paperboard Producing Process Attributes
- OP-UA62 Glycol Dehydration Unit Attributes
- OP-UA63 Vegetable Oil Production Attributes